

**1200SU-M**  
Single-Use Pump  
with Injected Molded  
Pump Chamber

Single-Use  
**Solutions** for  
Biotech &  
Pharmaceutical  
Applications

Responding to the voice of the customer, **Quattroflow™**  
1200SU Series Single-Use Quaternary  
Diaphragm Pumps

are now available with plastic pump chambers engineered with injected molded polyethylene (PE). Designed to be a more cost-effective solution, these next generation pump chambers save you time and money, removing the need for extensive cleaning, sterilization and complex cleaning validation.

**Features & Benefits:**

- About one-third lower in price than solid design polypropylene pump chambers
- Assembled under controlled and clean conditions
- Connections: 3/4" TC, front connections
- Max. pressure: 4 bar at 20°C (58 psi at 68°F)
- Range of flow: 6 – 1200 L/hr (1.6 – 317 gph)
- Max. temperature: 50°C (122°F), not autoclavable
- Chamber diameter: 119 mm (4.69 inch)
- Gamma irradiation possible

**For more information contact:**

ALMATEC Maschinenbau GmbH  
Hochstraße 150-152  
47228 Duisburg, Germany  
Tel: +49 (2065) 89205-0 • Fax: +49 (2065) 89205-40  
info@almatec.de  
[quattroflow.com](http://quattroflow.com)